

# AQUABION®

Galvanic Water Treatment  
Without chemicals or external power supply




## Technical sheet

### AQUABION® AB-F200



Pressure drop at type AB-F200



**Internal diameter** 8" DN200

Connection	flange
Length	445 mm
Body diameter	295 mm
Weight	90,96 kg
Maximum pressure	16 bar
Nominal flow at 2m/s	180,0 m <sup>3</sup> /h
Pressure drop at nominal flow	0,01 bar

#### 8-Holed Flanges

8"-Diameter of the Flange	340 mm
Circular Diameter of the Flangebores	295 mm
Flange Bore / Flange thickness	22 mm / 24 mm

**Material** **Body** GZ-CuZn35Al1 (2.0592.01)  
**Flange** G-CuZn35Al1 (2.0592.03)

Internal parts	Zinc anode	Zn2 DIN EN 1179
	Swirling body	1.4301
	Sealing ring	PTFE

**Construction** The body of the device consists of a single sleeve with two DIN flanges. The surface is nickel plated

<b>Temperatures of use</b>	Warm water:	
	- stored	60°C
	- circulating	60°C

**IMPORTANT:** AQUABION® must be installed in metal or plastic piping with metal piping before and after AQUABION® and with equipotential bonding.

